

DUAL-ZONE 36-INCH WINE CENTER



DZS36 Dual-Zone Wine Center with wine tapping.

NEW! Dual-Zone 36-inch Wine Center offers wine storage and tapping options in a compact size.

WINE  certified

Perfect fit, perfect pour.

The NEW Perlick single door **Dual-Zone Wine Center (DZS36)** has been specially designed to fit under a typical bar and features side-mounted refrigeration to reduce cabinet depth, making it a perfect fit for both new construction and retrofit applications.

Each compartment holds two 1/6 kegs. So even with limited space, your customers can capitalize on the growing demand for wine-by-the-glass.

Perlick[®]

DUAL-ZONE 36-INCH WINE CENTER

- The DZS36 features two separately programmable compartments to provide one digitally controlled temperature for white wines and another for reds. NSF-approved digital temperature control for each compartment offer a temperature range of more than 25 degrees – from 36 - 65°F – so your customers can serve vintages at the optimal temperature every time.
- Like the larger DZS60 within the same line of Perlick Wine Certified products, the DZS36 offers wine dispensing kits with sanitary 304 stainless steel components to protect the delicate flavors of fine vintages.
- Plus, unlike competitive models, the DZS36 fits under a typical bar, and the front refrigeration unit access means it's easy to service.



NUMBER OF DOORS		1
EXTERIOR CABINET DIMENSIONS	Length - in. (mm)	36 (914)
	Depth - in. (mm)	24.75 (629)
	Height - in. (mm)	34.565 (878)
INTERIOR CABINET DIMENSIONS	Length - in. (mm)	20 (508)
	Depth - in. (mm)	18.75 (476)
	Height - in. (mm)	28.5 (724)
INTERNAL VOLUME, Net. Cu. Ft. (liters)		7.1 (201)
SHIPPING WEIGHT, Lbs. (kg.)		305 (138)
ELECTRICAL SPECIFICATIONS	Electrical Supply	120 VAC/60 Hz/1 Ph
	Running Load Amps	3.2
	Electrical Connection	Connected
	Cord Plug Type	NEMA 5-15
	Cord Length	8'
	Defrost Initiation	Automatic
	Defrost Type	Off Cycle
	Thermostat	Digital Control
	Lighting Type	None

REFRIGERATION SPECIFICATIONS	Horsepower	1/5
	Refrigerant	R134a
	Refrigerant Charge	6.5
	Factory Temperature Setting - Refrigerator	38F (3.3C)
	Temperature Range - Refrigerator	34-42F (1.1-5.6C)
	Factory Temperature Setting - White Wine	45F (7.2C)
	Factory Temperature Setting - Red Wine	60F (15.6C)
	Temperature Range - Wine	40-65F (4.4-18.3C)
	Condensing Unit Location	Left or Right
	Expansion Device	Capillary Tube
	Pull-Out Condensing Unit	Yes
PLUMBING	Front Vented	Yes
	Floor Drain Included	No
	Evaporator Condensate	Automatically

Contact Perlick today to learn more about our line of Wine Certified wine dispensing options.



8300 West Good Hope Road, Milwaukee, Wisconsin 53223
perlick.com • 800.558.5592