



**24" ADA-HEIGHT COMPLIANT SERIES**  
*Refrigerator*



JOB	
AREA	
ITEM NO.	
MODEL NO.	



**Drawer Model**

MODELS	DESCRIPTION
<b>HA24RB-4-5</b>	Indoor ADA-Height Compliant Refrigerated Stainless Steel Drawers
<b>HA24RB-4-6</b>	Indoor ADA-Height Compliant Refrigerated Panel Ready Drawers

**KEY PRODUCT FEATURES AND BENEFITS**

- Superior construction provides ideal combination of energy efficient operation & powerful refrigeration performance ideal for food and beverages
- Industry's largest selection of ADA-height compliant models for accessible and aging in place designs
- 800 BTU/hr capacity delivers commercial grade cooling performance
- Commercial-grade all stainless steel interior provides superior durability and easy cleaning; black vinyl exterior for built in applications
- Smooth glide self closing drawers offer high storage capacity

**Quick Features:**

- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready drawers to match your design style
- Audible door alarm warns user if drawer is held open
- White LED task lighting
- R600a Refrigerant offers maximum energy efficiency with zero ozone depletion potential



**24" ADA-HEIGHT COMPLIANT SERIES**  
Refrigerator

MODEL NUMBERS		HA24RB
MODEL DESCRIPTION		24" Indoor ADA-Height Compliant Refrigerated Drawers
ATTRIBUTES		
Perlick Anti-Condensation System		NO
Energy Star Certified		YES
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8" (606 mm.)
	Depth - in. (mm)	24" (610 mm.)
	Height - in. (mm)	32" (813 mm.)
STANDARD OPENING DIMENSIONS	Width - in. (mm)	24" (610 mm.)
	Depth - in. (mm)	24-7/8" (632 mm.)
	Height - in. (mm)	32-1/4" (819 mm.)
INTERNAL VOLUME Net. Cu. Ft.		4.8 cu. ft total
SHIPPING WEIGHT Lbs. (kg.)		181 lbs (82.27 kg.)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph
	Running Load Amps	1.9 amps
	Electrical Connection	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P
	Cord Length	6'
	Defrost Initiation	Automatic
	Defrost Type	Off cycle
	Thermostat	Digital
	Lighting Type	LED
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (62g)
	Expansion Device	Capillary Tube
	Temperature Settings F°(C°)	33° (0.5°) - 48° (8.8°) <b>Factory Set Point 36° (2.2°)</b>
	Heat Rejection (at 75°F)	450 BTU/hr
	Pull Down Capacity	800 BTU/hr
	Front Vented	Yes
PLUMBING		None Required

*Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.*

**ACCESSORIES**

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
67164	6" Toe Kick Kit (includes riser) for HA24 models
66736	Caster Kit for HP24/HC24/HA24 models
RS-24-24D	Divider Shelf for HP24/HC24/HA24 models

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit [perlick.com](http://perlick.com).



**WARNING: California Prop 65 Notice**

These products may expose you to chemicals including Chromium, which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information on whether a product in this list contains these chemicals, please refer to the specific product page at [perlick.com](http://perlick.com). Or to find out more about **Prop 65**, go to [P65Warnings.ca.gov](http://P65Warnings.ca.gov).



**24" ADA-HEIGHT COMPLIANT SERIES**  
Refrigerator

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HA24RB-4-5	HA24RB4E-00-EDS0D	Drawers	No
HA24RB-4-6	HA24RB4E-00-DD00D	Drawers	No
HA24RB-4-5DL	HA24RB4E-00-EDSLD	Drawers	Yes
HA24RB-4-6DL	HA24RB4E-00-DD0LD	Drawers	Yes

