Perlick®

24" ADA-HEIGHT COMPLIANT SERIES
Refrigerator

C (UL) US   ENERGY STAR   6 YEAR WARRANTY   ♿✓

JOB	
AREA	
ITEM NO.	
MODEL NO.	

Glass Door Model

Solid Door Model

MODELS	DESCRIPTION
HA24RB-4-1R/L	Indoor ADA-Height Compliant Refrigerator Solid Stainless Steel Door
HA24RB-4-2R/L	Indoor ADA-Height Compliant Refrigerator Solid Panel Ready Door
HA24RB-4-3R/L	Indoor ADA-Height Compliant Refrigerator Stainless Steel Glass Door
HA24RB-4-4R/L	Indoor ADA-Height Compliant Refrigerator Panel Ready Glass Door

KEY PRODUCT FEATURES AND BENEFITS

- Superior construction provides ideal combination of energy efficient operation & powerful refrigeration performance ideal for food and beverages
- Industry's largest selection of ADA-height compliant models for accessible and aging in place designs
- 800 BTU/hr capacity delivers commercial grade cooling performance
- Commercial-grade all stainless steel interior provides superior durability and easy cleaning; black vinyl exterior for built in applications
- Full extension shelving provides faster and safer product access with no reaching in the back of the cabinet; shelves fully extend on vibration dampened stainless steel ball-bearing glides

Quick Features:

- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready door to match your design style
- Audible door alarm warns user if door is held open
- Selectable blue or white LED lighting
- R600a Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Storage for up to 108 cans

Perlick®

24" ADA-HEIGHT COMPLIANT SERIES
Refrigerator

MODEL NUMBERS		HA24RB
MODEL DESCRIPTION		24" Indoor ADA-Height Compliant Refrigerator
ATTRIBUTES		
Perlick Anti-Condensation System		NO
Energy Star Certified		YES
OVERALL DIMENSIONS	**Width - in. (mm)**	23-7/8" (606 mm.)
	Depth - in. (mm)	24" (610 mm.)
	Height - in. (mm)	32" (813 mm.)
STANDARD OPENING DIMENSIONS	**Width - in. (mm)**	24" (610 mm.)
	Depth - in. (mm)	24-7/8" (632 mm.)
	Height - in. (mm)	32-1/4" (819 mm.)
INTERNAL VOLUME Net. Cu. Ft. (L)		4.8 cu. ft total
SHIPPING WEIGHT Lbs. (kg.)		181 lbs (82.27 kg.)
ELECTRICAL SPECIFICATIONS	**Electrical Supply**	115 VAC/60 Hz/1 Ph
	Running Load Amps	1.9 amps
	Electrical Connection	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P
	Cord Length	6'
	Defrost Initiation	Automatic
	Defrost Type	Off cycle
	Thermostat	Digital
	Lighting Type	LED
REFRIGERATION SPECIFICATIONS	**Refrigerant**	R600a (62g)
	Expansion Device	Capillary Tube
	Temperature Settings F°(C°)	33° (0.5°) - 48° (8.8°) **Factory Set Point** 36° (2.2°)
	Heat Rejection (at 75°F)	450 BTU/hr
	Pull Down Capacity	800 BTU/hr
	Front Vented	Yes
PLUMBING		None Required

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

ACCESSORIES

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
67164	6" Toe Kick Kit (includes riser) for HA24 models
66736	Caster Kit for HP24/HC24/HA24 models
RS-24-24D	Divider Shelf for HP24/HC24/HA24 models

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit **perlick.com.**

⚠ **WARNING: California Prop 65 Notice**
These products may expose you to chemicals including Chromium, which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information on whether a product in this list contains these chemicals, please refer to the specific product page at perlick.com. Or to find out more about **Prop 65**, go to **P65Warnings.ca.gov**.

Perlick®
24" ADA-HEIGHT COMPLIANT SERIES
Refrigerator

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HA24RB-4-1L	HA24RB4C-00-SLS0R	Left	No
HA24RB-4-1R	HA24RB4C-00-SRS0R	Right	No
HA24RB-4-2L	HA24RB4C-00-PL00R	Left	No
HA24RB-4-2R	HA24RB4C-00-PR00R	Right	No
HA24RB-4-3L	HA24RB4C-00-TLS0R	Left	No
HA24RB-4-3R	HA24RB4C-00-TRS0R	Right	No
HA24RB-4-4L	HA24RB4C-00-RL00R	Left	No
HA24RB-4-4R	HA24RB4C-00-RR00R	Right	No
HA24RB-4-1LL	HA24RB4C-00-SLSLR	Left	Yes
HA24RB-4-1RL	HA24RB4C-00-SRSLR	Right	Yes
HA24RB-4-2LL	HA24RB4C-00-PL0LR	Left	Yes
HA24RB-4-2RL	HA24RB4C-00-PR0LR	Right	Yes
HA24RB-4-3LL	HA24RB4C-00-TLSLR	Left	Yes
HA24RB-4-3RL	HA24RB4C-00-TRSLR	Right	Yes
HA24RB-4-4LL	HA24RB4C-00-RL0LR	Left	Yes
HA24RB-4-4RL	HA24RB4C-00-RR0LR	Right	Yes

Perlick®
24" ADA-HEIGHT COMPLIANT SERIES
Refrigerator

50"
AREA IN WHICH ELECTRICAL OUTLET MUST BE LOCATED

$10\frac{7}{8}$"

POWER CORD 6-3/8" OFF FLOOR

90.0°

$24\frac{15}{16}$"
MIN CLEARANCE
FOR DOOR SWING

$1\frac{3}{8}$"
CLEARANCE FROM HINGE
SIDE OF CABINET WHEN
LOCATING UNIT IN A CORNER
TO ALLOW ACCESS TO FULL
EXTENSION SHELVES

$23\frac{7}{8}$"

20"

$20\frac{3}{4}$"

32"

$3\frac{1}{2}$"

$3\frac{7}{8}$"

$1\frac{3}{8}$"
VALUE MAY
CHANGE DUE
TO CUSTOM PULL

24" +/- 1/16"
VALUE MAY CHANGE WITH
A WOOD OVERLAY DOOR

$18\frac{1}{2}$"

$1\frac{5}{8}$"
CONTROL
HEIGHT

$1\frac{1}{8}$"
SHELF
ADJUSTABILITY

$22\frac{5}{8}$"

$19\frac{1}{8}$"

$4\frac{15}{16}$"
LOWEST SHELF
LOCATION

$11\frac{7}{8}$"

$6\frac{9}{16}$"