



**24" GLASS CHILLER**

eco friendly  
R600a Refrigerant



**5 Year**  
Compressor  
Warranty



JOB	
AREA	
ITEM NO.	
MODEL NO.	

<b>MODEL NO.</b>
HC24FS-SS-STK



**HC24FS-SS-STK**

**KEY PRODUCT FEATURES AND BENEFITS**

- All stainless steel interior ensures consistent cabinet temperature and hygienic easy to clean environment that will not absorb odors over time
- Full extension, smooth glide shelving gives easy access to product and faster, more ergonomic product loading
- Ultra-quiet and energy efficient smart compressor – compressor ramps up as additional cooling is needed maximizing energy savings while decreasing pull down time
- NSF rated digital controller allows for precision temperature setting and features and audible door alarm, alerting the operator if an intrusion will not allow the door to close
- Open shelf design allows cold air to surround product reducing temperature variation in the cabinet and extending product life
- 525 BTU/hr fast pull down of product to serving temperature

**Quick Features:**

- 2" foamed-in-place eco-friendly insulation provides energy savings with zero ozone depletion
- Smart defrost cycle runs only when needed, increasing energy efficiency over standard systems
- Selectable white or blue LEDs provide crisp line of sight to product
- Custom door are customer supplied – see perlick.com for door overlay templates
- Field reversible door allows for easy replacement or re-purposing
- Door lock standard to secure contents
- NSF 7 rated for canned and bottle beverage storage
- No plumbing required
- 1 Year Warranty, 5 Year Compressor Warranty



**24" GLASS CHILLER**

<b>MODEL NO.</b>		<b>HC24FS-SS-STK</b>
<b>CABINET DIMENSIONS</b>	Length Ins. (mm)	23-7/8" (606)
	Depth Ins. (mm)	24" (610)
	Height Ins. (mm)	34" (864)
<b>SHIP WEIGHT LBS. (KG)</b>		195 (88)
<b>CAPACITY CU. FT. (L.) [PRODUCT*]</b>		5.3 (150) [86 glasses]
<b>SHELVING</b>		2 black vinyl-coated full-extension shelf (adjustable)
<b>TEMPERATURE SETTINGS F°(C°)</b>		-10° (-23.3°) - 10° (-12.2°) <b>Factory Set Point 0° (-17.8°)</b>
<b>CABINET CONSTRUCTION (INT.)</b>		<b>Interior</b> Stainless Steel
<b>CABINET CONSTRUCTION (EXT.)</b>		<b>Exterior Sides, Exterior Top and Grill</b> Stainless Steel <b>Exterior Back and Exterior Bottom</b> Galvanized
<b>CABINET INSULATION</b>		Polyurethane-Ecomate. <b>Wall Thickness 2" Door, Drawer Thickness 2"</b> (solid stainless steel only)
<b>DOORS, HINGING &amp; HARDWARE</b>		<b>Number of Doors 1 Opening Style</b> Hinged Left <b>Door Style</b> Solid <b>Door Swing Clearance 25"</b> (635)
<b>CONDENSING UNIT</b>		Condenser Access Front
<b>REFRIGERATION</b>		<b>Refrigerant</b> R600a: 62g <b>Expansion Device</b> Capillary Tube Type w/Hermetic Compressor <b>Defrost</b> Automatic 4-hour hot gas defrost cycle
<b>HEAT REJECTION (at 75°F ambient)</b>		700 BTU/hr
<b>PULL DOWN CAPACITY</b>		525 BTU/hr
<b>PLUMBING</b>		None required. Moisture drains to self evaporating condensate pan
<b>ELECTRICAL</b>		<b>Electrical Supply</b> 115V/60 Hz/1 Phase <b>Running Load Amps 1.9 Cord Connection</b> Cord Connected (3-prong 6' NEMA 5-15P) <b>Thermostat</b> Digital <b>Lighting Type</b> LED
<b>VENTILATION</b>		Front-vented
<b>ADDITIONAL ACCESSORIES</b>		<b>Casters</b> 3.75" (Part No. 66736) <b>Legs</b> 4"-5" (Part No. 66734), 6"-7.25" (Part. No 66735)

\*Product capacity based on 3" diameter glass size

**NOTE:** This equipment is intended for the storage and display of non-potentially hazardous bottled or canned products only!

**! WARNING: California Prop 65 Notice**

These products may expose you to chemicals including Chromium, which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information on whether a product in this list contains these chemicals, please refer to the specific product page at [perlick.com](http://perlick.com). Or to find out more about Prop 65, go to [P65Warnings.ca.gov](http://P65Warnings.ca.gov).



24" GLASS CHILLER

