



SIGNATURE SERIES SHALLOW DEPTH
18" Depth Beverage Center



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Glass Door Model



Solid Door Model

MODELS	DESCRIPTION
HH24BS-4-1R/L	Indoor Shallow Depth Beverage Center Solid Stainless Steel Door
HH24BS-4-2R/L	Indoor Shallow Depth Beverage Center Solid Panel Ready Door
HH24BS-4-3R/L	Indoor Shallow Depth Beverage Center Stainless Steel Glass Door
HH24BS-4-4R/L	Indoor Shallow Depth Beverage Center Panel Ready Glass Door
HH24BO-4-1R/L	Outdoor Shallow Depth Beverage Center Solid Stainless Steel Door
HH24BO-4-2R/L	Outdoor Shallow Depth Beverage Center Solid Panel Ready Door
HH24BO-4-3R/L	Outdoor Shallow Depth Beverage Center Stainless Steel Glass Door
HH24BO-4-4R/L	Outdoor Shallow Depth Beverage Center Panel Ready Glass Door
HH24BM-4-1R/L	Marine Shallow Depth Beverage Center Solid Stainless Steel Door
HH24BM-4-2R/L	Marine Shallow Depth Beverage Center Solid Panel Ready Door
HH24BM-4-3R/L	Marine Shallow Depth Beverage Center Stainless Steel Glass Door
HH24BM-4-4R/L	Marine Shallow Depth Beverage Center Panel Ready Glass Door

KEY PRODUCT FEATURES AND BENEFITS

- Industry's first 18" shallow depth for ultimate design flexibility in tight spaces
- Industry's largest selection of ADA-height compliant models for accessible and aging in place designs
- Superior construction provides ideal combination of energy efficient operation & powerful refrigeration performance ideal for food and beverages
- 1000 BTU/hr capacity delivers industry's most energy efficient cool down; indoors or outdoors
- Up to 70% faster cooling speeds than leading competitor
- All stainless steel interior and exterior provide superior durability and easy cleaning
- Two wine and one refrigerator shelf fully extend on vibration dampened, stainless steel ball-bearing glides; stainless steel wine shelves will not absorb odors over time
- Perlick Anti-Condensation System™ eliminates condensation from forming on the cabinet (Outdoor and Marine models only)
- Marine & Coastal Grade with Perlick Armor™ upgrades stainless steel, fasteners, and refrigeration system to the highest blend of corrosion resistance and food safety

Quick Features:

- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready door to match your design style
- Audible door alarm warns user if door is held open
- Selectable blue or white LED lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Storage for up to 41 cans and 10 bottles of wine



SIGNATURE SERIES SHALLOW DEPTH
18" Depth Beverage Center

MODEL NUMBERS		HH24BS	HH24BO	HH24BM
MODEL DESCRIPTION		18" Indoor Beverage Center	18" Outdoor Beverage Center	18" Marine Beverage Center
ATTRIBUTES				
Perlick Anti-Condensation System		NO	YES	YES
Energy Star Certified		YES	YES	YES
Perlick Armor™		NO	NO	YES
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8" (606 mm)	23-7/8" (606 mm)	23-7/8" (606 mm)
	Depth - in. (mm)	18" (457 mm)	18" (457 mm)	18" (457 mm)
	Height - in. (mm)	32" (813 mm)	32" (813 mm)	32" (813 mm)
STANDARD OPENING DIMENSIONS	Width - in. (mm)	24" (610 mm)	24" (610 mm)	24" (610 mm)
	Depth - in. (mm)	18" (457 mm)	18" (457 mm)	18" (457 mm)
	Height - in. (mm)	32-1/4" (819 mm)	32-1/4" (819 mm)	32-1/4" (819 mm)
INTERNAL VOLUME Net. Cu. Ft.		3.1 cu. ft.	3.1 cu. ft.	3.1 cu. ft.
SHIPPING WEIGHT Lbs. (kg.)		185 lbs (83.91 kg)	185 lbs (83.91 kg)	185 lbs (83.91 kg)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph
	Running Load Amps	1.9 amps	1.9 amps	1.9 amps
	Electrical Connection	Cord connected	Cord connected	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P
	Cord Length	6'	6'	6'
	Defrost Initiation	Automatic	Automatic	Automatic
	Defrost Type	Off cycle	Off cycle	Off cycle
	Thermostat	Digital	Digital	Digital
	Lighting Type	LED	LED	LED
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a(62g)	R600a(62g)	R600a(62g)
	Expansion Device	Capillary Tube	Capillary Tube	Capillary Tube
	Temperature Settings F°(C°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)
	Heat Rejection (at 75°F)	350 BTU/hr	350 BTU/hr	350 BTU/hr
	Pull Down Capacity	1000 BTU/hr	1000 BTU/hr	1000 BTU/hr
	Front Vented	Yes	Yes	Yes
PLUMBING		None Required	None Required	None Required

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

ACCESSORIES

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
67992-L/R	Stacking Kit for HH24 models
67115-24	Wood Faces for Wine Shelves (7/pk)
67360	6" Toe Kick and Riser

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com.



WARNING: California Prop 65 Notice

These products may expose you to chemicals including Chromium, which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information on whether a product in this list contains these chemicals, please refer to the specific product page at perlick.com. Or to find out more about **Prop 65**, go to P65Warnings.ca.gov.



SIGNATURE SERIES SHALLOW DEPTH
18" Depth Beverage Center

	CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
INDOOR	HH24BS-4-1L	HH24BS4C-00-SLF0B	Left	No
	HH24BS-4-1R	HH24BS4C-00-SRF0B	Right	No
	HH24BS-4-2L	HH24BS4C-00-PL00B	Left	No
	HH24BS-4-2R	HH24BS4C-00-PR00B	Right	No
	HH24BS-4-3L	HH24BS4C-00-TLF0B	Left	No
	HH24BS-4-3R	HH24BS4C-00-TRF0B	Right	No
	HH24BS-4-4L	HH24BS4C-00-RL00B	Left	No
	HH24BS-4-4R	HH24BS4C-00-RR00B	Right	No
	HH24BS-4-1LL	HH24BS4C-00-SLFLB	Left	Yes
	HH24BS-4-1RL	HH24BS4C-00-SRFLB	Right	Yes
	HH24BS-4-2LL	HH24BS4C-00-PL0LB	Left	Yes
	HH24BS-4-2RL	HH24BS4C-00-PR0LB	Right	Yes
	HH24BS-4-3LL	HH24BS4C-00-TLFLB	Left	Yes
	HH24BS-4-3RL	HH24BS4C-00-TRFLB	Right	Yes
	HH24BS-4-4LL	HH24BS4C-00-RL0LB	Left	Yes
	HH24BS-4-4RL	HH24BS4C-00-RR0LB	Right	Yes
OUTDOOR	HH24BO-4-1L	HH24BO4C-00-SLF0B	Left	No
	HH24BO-4-1R	HH24BO4C-00-SRF0B	Right	No
	HH24BO-4-2L	HH24BO4C-00-PL00B	Left	No
	HH24BO-4-2R	HH24BO4C-00-PR00B	Right	No
	HH24BO-4-3L	HH24BO4C-00-TLF0B	Left	No
	HH24BO-4-3R	HH24BO4C-00-TRF0B	Right	No
	HH24BO-4-4L	HH24BO4C-00-RL00B	Left	No
	HH24BO-4-4R	HH24BO4C-00-RR00B	Right	No
	HH24BO-4-1LL	HH24BO4C-00-SLFLB	Left	Yes
	HH24BO-4-1RL	HH24BO4C-00-SRFLB	Right	Yes
	HH24BO-4-2LL	HH24BO4C-00-PL0LB	Left	Yes
	HH24BO-4-2RL	HH24BO4C-00-PR0LB	Right	Yes
	HH24BO-4-3LL	HH24BO4C-00-TLFLB	Left	Yes
	HH24BO-4-3RL	HH24BO4C-00-TRFLB	Right	Yes
	HH24BO-4-4LL	HH24BO4C-00-RL0LB	Left	Yes
	HH24BO-4-4RL	HH24BO4C-00-RR0LB	Right	Yes
MARINE & COASTAL	HH24BM-4-1L	HH24BM4C-00-MLF0B	Left	No
	HH24BM-4-1R	HH24BM4C-00-MRF0B	Right	No
	HH24BM-4-2L	HH24BM4C-00-PL00B	Left	No
	HH24BM-4-2R	HH24BM4C-00-PR00B	Right	No
	HH24BM-4-3L	HH24BM4C-00-NLF0B	Left	No
	HH24BM-4-3R	HH24BM4C-00-NRF0B	Right	No
	HH24BM-4-4L	HH24BM4C-00-RL00B	Left	No
	HH24BM-4-4R	HH24BM4C-00-RR00B	Right	No
	HH24BM-4-1LL	HH24BM4C-00-MLFLB	Left	Yes
	HH24BM-4-1RL	HH24BM4C-00-MRFLB	Right	Yes
	HH24BM-4-2LL	HH24BM4C-00-PL0LB	Left	Yes
	HH24BM-4-2RL	HH24BM4C-00-PR0LB	Right	Yes
	HH24BM-4-3LL	HH24BM4C-00-NLFLB	Left	Yes
	HH24BM-4-3RL	HH24BM4C-00-NRFLB	Right	Yes
	HH24BM-4-4LL	HH24BM4C-00-RL0LB	Left	Yes
	HH24BM-4-4RL	HH24BM4C-00-RR0LB	Right	Yes



SIGNATURE SERIES SHALLOW DEPTH
18" Depth Beverage Center

