







| JOB       |  |
|-----------|--|
| AREA      |  |
| ITEM NO.  |  |
| MODEL NO. |  |





| Available with 1 or 2 faucets |
|-------------------------------|
| (2 faucet shown)              |

| MODELS   | DESCRIPTION   |  |
|--|---|--|
| <b>HP24TS-4-1L/R-1A</b> Indoor Signature Series Adara Beverage Dispenser Solid Stainless Steel Door 1 Fauc |   |  |
| HP24TS-4-2L/R-1A   | HP24TS-4-2L/R-1A Indoor Signature Series Adara Beverage Dispenser Solid Panel Ready Door 1 Faucet |  |
| <b>HP24TS-4-1L/R-2A</b> Indoor Signature Series Adara Beverage Dispenser Solid Stainless Steel Door 2 Fau  |   |  |
| <b>HP24TS-4-2L/R-2A</b> Indoor Signature Series Adara Beverage Dispenser Solid Panel Ready D               |   |  |

## **KEY PRODUCT FEATURES AND BENEFITS**

- Superior construction provides ideal combination of energy efficient operation & powerful refrigeration performance ideal for kegged beverages
- 1000 BTU/hr capacity delivers industry's most energy efficient cool down; indoors or outdoors
- Up to 70% faster cooling speeds than leading competitor
- All stainless steel interior and exterior provide superior durability and easy cleaning
- Forced air refrigeration technology ensures consistent temperature throughout entire keg, maintaining flavor better than other brands

## **Quick Features:**

- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready doors to match your design style
- Audible door alarm warns user if door is held open
- · White LED task lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Accommodates two (2) 1/6 barrels or one (1) 1/4 slim or standard barrel







Two 1/6 barrel



| MODEL NUMBERS                    |                             | HP24TS  |  |
|----------------------------------|-----------------------------|---|--|
| MODEL DESCRIPTION                |                             | 24" Indoor Beverage Dispenser - Adara Tower             |  |
| ATTRIBUTES                       |                             |   |  |
| Perlick Anti-Condensation System |                             | NO  |  |
| Energy Star Certified            |                             | YES   |  |
|                                  | Width - in. (mm)            | 23-7/8" (606 mm.)                                       |  |
| OVERALL DIMENSIONS               | Depth - in. (mm)            | 24" (610 mm.)   |  |
|                                  | Height - in. (mm)           | 34-1/4" (870 mm.)                                       |  |
|                                  | Width - in. (mm)            | 24" (610 mm.)   |  |
| STANDARD OPENING DIMENSIONS      | Depth - in. (mm)            | 24-7/8" (632 mm.)                                       |  |
|                                  | Height - in. (mm)           | 34-1/2" (876 mm.)                                       |  |
| INTERNAL VOLUME Net. Cu. Ft.     |                             | 5.2 cu. ft.   |  |
| SHIPPING WEIGHT Lbs. (kg.)       |                             | 222 lbs (100.7 kg.)                                     |  |
|                                  | Electrical Supply           | 115 VAC/60 Hz/1 Ph                                      |  |
|                                  | Running Load Amps           | 1.9 amps  |  |
|                                  | Electrical Connection       | Cord connected  |  |
|                                  | Cord Plug Type              | NEMA 3 Prong 5-15P                                      |  |
| ELECTRICAL SPECIFICATIONS        | Cord Length                 | 6′  |  |
|                                  | Defrost Initiation          | Automatic   |  |
|                                  | Defrost Type                | Off cycle   |  |
|                                  | Thermostat                  | Digital   |  |
|                                  | Lighting Type               | LED   |  |
|                                  | Refrigerant                 | R600a (62g)   |  |
|                                  | Expansion Device            | Capillary Tube  |  |
| REFRIGERATION SPECIFICATIONS     | Temperature Settings F°(C°) | 33° (0.5°) - 48° (8.8°)<br>Factory Set Point 36° (2.2°) |  |
|                                  | Heat Rejection (at 75°F)    | 450 BTU/hr  |  |
|                                  | Pull Down Capacity          | 1000 BTU/hr   |  |
|                                  | Front Vented                | Yes   |  |
| PLUMBING                         |                             | None Required   |  |

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

## **ACCESSORIES**

| MODEL NOS. | DESCRIPTION                                |  |
|------------|--|--|
| (L)        | Factory Installed Lock                     |  |
| 66736      | Caster Kit for HP24/HC24/HA24 models       |  |
| 63797      | Beer Dispenser Cleaning Kit                |  |
| 40030S     | Low Profile Keg Coupler                    |  |
| 67141-1    | Perlick Faucet Handle                      |  |
| BLC4/32    | Beer Dispenser Sanitizer (4 oz. or 32 oz.) |  |

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com.



## WARNING: California Prop 65 Notice

These products may expose you to chemicals including Chromium, which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information on whether a product in this list contains these chemicals, please refer to the specific product page at perlick.com. Or to find out more about Prop 65, go to P65Warnings.ca.gov.



| CUSTOMER MODEL NUMBER | REGULATORY MODEL NUMBER | Hinge Side | Lock |
|-----------------------|-------------------------|------------|------|
| HP24TS-4-1L-1A        | HP24TS4C-E0-SLF0T       | Left       | No   |
| HP24TS-4-1R-1A        | HP24TS4C-E0-SRF0T       | Right      | No   |
| HP24TS-4-2L-1A        | HP24TS4C-E0-PL00T       | Left       | No   |
| HP24TS-4-2R-1A        | HP24TS4C-E0-PR00T       | Right      | No   |
| HP24TS-4-1L-2A        | HP24TS4C-F0-SLF0T       | Left       | No   |
| HP24TS-4-1R-2A        | HP24TS4C-F0-SRF0T       | Right      | No   |
| HP24TS-4-2L-2A        | HP24TS4C-F0-PL00T       | Left       | No   |
| HP24TS-4-2R-2A        | HP24TS4C-F0-PR00T       | Right      | No   |
| HP24TS-4-1LL-1A       | HP24TS4C-E0-SLFLT       | Left       | Yes  |
| HP24TS-4-1RL-1A       | HP24TS4C-E0-SRFLT       | Right      | Yes  |
| HP24TS-4-2LL-1A       | HP24TS4C-E0-PL0LT       | Left       | Yes  |
| HP24TS-4-2RL-1A       | HP24TS4C-E0-PR0LT       | Right      | Yes  |
| HP24TS-4-1LL-2A       | HP24TS4C-F0-SLFLT       | Left       | Yes  |
| HP24TS-4-1RL-2A       | HP24TS4C-F0-SRFLT       | Right      | Yes  |
| HP24TS-4-2LL-2A       | HP24TS4C-F0-PL0LT       | Left       | Yes  |
| HP24TS-4-2RL-2A       | HP24TS4C-F0-PR0LT       | Right      | Yes  |



