



MODEL NUMBERS - PKHT24A,

HIGH TEMPERATURE GLASS WASHER



PKHT24A

| | |
|-----------|--|
| JOB | |
| AREA | |
| ITEM NO. | |
| MODEL NO. | |

| |
|---------------|
| MODELS |
| PKHT24A |

FEATURES AND BENEFITS

- Removes lipstick and other residue for the cleanest glasses
- All stainless steel construction with 16-gauge stainless steel wash tank
- Cleans and sanitizes 28 racks per hour
- Uses only .68 gallons of water per cycle
- 2 minute timer includes the built-in, automatic Safe-T-Temp feature, which assures a 180°F sanitizing final rinse
- Detergent and rinse chemical pumps
- Fresh water rinse through upper and lower arms – rotating arms provide maximum glass surface coverage
- Built in drain pump, booster & in-wash heaters, chemical dispensers, & delime switch

SHORT DESCRIPTION

- Top-mounted controls for easy operation and temperature monitoring
- Unit comes standard with 4" legs raising total height of equipment to 37.25"-38.25"
- Removable stainless steel pump protection screen for easy cleaning
- Large 14-1/2-inch door opening to accommodate larger glasses, dishes, and half size sheet pans

OPTIONS

| MODEL NOS. | DESCRIPTION |
|------------|------------------------------|
| PKHT24A | High Temperature Glasswasher |

Form No. PKHT24A.1
Rev. 05.08.25



PERLICK®



MODEL NUMBERS – PKHT24A,

HIGH TEMPERATURE GLASS WASHER

| MODEL NOS. | | PKHT24A |
|---|--|---|
| DIMENSIONS: EXTERIOR (mm) | Depth | 25" (635) |
| | Width | 24" (610) |
| | Height | 33-1/4" (845) |
| | Maximum Clearance For Dishes | 14-1/2" (286) |
| | Weight Lbs. (kg) | 234 (106) |
| ELECTRICAL RATING* Must connect to 40 amp supply circuit. | Volts / Hz | 208V / 240V 1PH-60Hz |
| | Total Amps | 30A / 32A |
| | Booster Heater KW | 5.3kW / 6.5kW |
| WATER CONSUMPTION, GALLONS (LITERS) | Per Rack | .68 (2.57) |
| | Per Hour | 19 (72.1) |
| OPERATING CYCLE | Wash Time, Seconds | 99 |
| | Sanitizer Time, Seconds | 11 |
| | Dwell Time, Seconds | 10 |
| | Total Cycle Time | 2 Minutes |
| OPERATING CAPACITY | Racks Per Hour | 28 |
| | Wash Tank Capacity, Gallons (lt) | 2.5 (9.46) |
| | Pump Capacity, Gallons per Minute (lt) | 38 (144) |
| WATER REQUIREMENTS | Required Minimum Temperature* | 120°F (43°C) |
| | Recommended Temperature** | 140°F (60°C) |
| | Water Inlet, Inches (cm) | 1/2 NPTM (1.27) |
| | Drain Connection, Inches (cm) | 1 (2.54) IPS PVC socket to include an air gap |
| | Rinse Pressure Set | 20 +/- 5psi / (1.41 kg/cm²) |
| CYCLE TEMPERATURES | Wash | 160°F minimum (65.5-71°C) |
| | Rinse | 180-195°F (82-90°C) |
| WASH PUMP MOTOR | | 3/4 HP |
| ENERGY STAR RATING | | 3.0 |
| AVAILABLE OPTION | Second year extended parts and labor warranty (includes one (1) year parts and labor warranty) | |

NOTE: This system requires three power wires, which includes a current- carrying neutral wire. An additional fourth wire must be provided for grounding the machine.

* For machine having Safety-Temp feature

** For faster heat recovery